


HORIZONTAL OPENWELL SUBMERSIBLE PUMPS				 Pareesh Submersible Pump Set
APPROXIMATE PERFORMANCE DATA AT 2880 RPM, 380-415 VOLTS, THREE PHASE, 50 Hz, A.C. SUPPLY				

Pump Model	H.P.	Outlet Size	Cable SQ. M.M.	Horizontal Openwell Capacity in LPM at various Head in Meters													
				12	14	18	22	24	26	28	32	36	38	40	46	50	
PHS3LH	3.0	65X50	1x3x1.5	770	710	575	450	-	-	-	-	-	-	-	-	-	-
PHS3HH	3.0	65X50	1x3x1.5	-	680	575	460	375	290	-	-	-	-	-	-	-	-
PHS5LH	5.0	65X65	1x3x1.5	-	995	910	750	650	575	500	-	-	-	-	-	-	-
PHS5HH	5.0	65X50	1x3x1.5	-	-	715	690	650	610	575	450	290	115	-	-	-	-
PHS7.5LH	7.5	65X65	1x3x2.5	-	1270	1230	1200	1120	1025	945	709	-	-	-	-	-	-
PHS7.5HH	7.5	65X50	1x3x2.5	-	-	-	810	750	670	650	625	590	550	515	320	-	-
PHS10LH	10	100X100	2x3x2.5	-	-	1820	1530	1400	1205	-	-	-	-	-	-	-	-
PHS10HH	10	65X50	2x3x2.5	-	-	-	-	-	-	-	-	900	805	775	740	620	500

DECLARATION

We here by declare that the details shown in the performance table are as per the verified test reports and tested under standard test conditions of supply voltage, frequency and rated speed of the motors with allowing permissible allowances.